

DCN-FVU Flush Voting Unit

www.boschsecurity.com



BOSCH
Invented for life



- ▶ Stylish and modern design (IF award)
- ▶ Allows parliamentary voting, numerals and rating scale
- ▶ Easily mountable
- ▶ Direct loop through connection to the DCN network
- ▶ Economic solution for positions which only require voting facilities

The Flush Voting Unit allows attendance registration and six types of voting: parliamentary, audience response, multiple choice, opinion poll, rating and for/against.

The yellow LED confirmation indicators prompt the user to indicate presence and to vote and to confirm registration of what is voted.

The blue LED unit active indicator shows that the system is in normal operation. The blue LED flashes when the unit detects a communication fault.

The combination of the voting unit with the end caps forms a very stylish design, which fits in both modern and traditional meeting rooms.

The direct connection to the DCN network cable results into an economic solution for positions which only require voting facilities

Functions

Controls and Indicators

Front

- Five voting buttons with yellow confirmation indicators to prompt the user to indicate presence, to vote and to confirm registration of what is voted. The buttons and indicators work as follows:

- Yes (+), no (-) and abstain (x) (used for attendance registration, parliamentary voting and for/against)
- Numerals 1 to 5 (used for multiple choice, opinion polls and rating)
- Rating scale: --, -, 0, +, ++ (used for audience response)

- One unit active indicator. A constant lit blue LED indicates that the system is in normal operation. The blue LED flashes when the unit detects a communication fault

Back

- One de-init/init button

Interconnections

- 1 m (39.4 in) DCN cable terminated with a molded six-pole male circular connector
- 1 m (39.4 in) DCN cable terminated with a molded six-pole female circular connector for loop-through connection to the DCN network



Notice

An unused output cable must be terminated with an LBB 4118/00 Termination Plug.

Technical specifications

Mechanical

Mounting	Click-to-fit in a metal panel with a thickness of 2 mm, or in combination with DCN-FCOUP couplings and DCN-FEC end caps in any surrounding
Dimensions (H x W x D)	40 x 100 x 79.42 mm (1.57 x 3.94 x 3.12 in)
Weight	250 g (0.55 lb)
Color	
DCN-FVU	Silver (RAL 9022)
DCN-FVU-D	Dark (graphite gray)

Ordering information

DCN-FVU Flush Voting Unit

direct loop-through connection to DCN network, flush mounted, silver

Order number **DCN-FVU**

DCN-FVU-D Flush Voting Unit Dark

direct loop-through connection to DCN network, flush mounted, dark

Order number **DCN-FVU-D**

LBB 4118/00 DCN Termination Plug

use with opened-ended DCN cabling

Order number **LBB4118/00**

Represented by:

Americas:

Bosch Security Systems, Inc.
12000 Portland Avenue South
Burnsville MN 55337, USA
Phone: +1-800-392-3497
Fax: +1-800-955-6831
audiosupport@us.bosch.com
www.boschsecurity.com

Europe, Middle East, Africa:

Bosch Security Systems B.V.
P.O. Box 80002
5617 BA Eindhoven, The Netherlands
Phone: + 31 40 2577 284
Fax: +31 40 2577 330
emea.securitysystems@bosch.com
www.boschsecurity.com

Asia-Pacific:

Robert Bosch (SEA) Pte Ltd, Security Systems
11 Bishan Street 21
Singapore 573943
Phone: +65 6571 2808
Fax: +65 6571 2699
apr.securitysystems@bosch.com
www.boschsecurity.asia

China:

Bosch (Shanghai) Security Systems Ltd.
201 Building, No. 333 Fuquan Road
North IBP
Changning District, Shanghai
200335 China
Phone +86 21 22181111
Fax: +86 21 22182398
www.boschsecurity.com.cn

America Latina:

Robert Bosch Ltda Security Systems Division
Via Anhanguera, Km 98
CEP 13065-900
Campinas, Sao Paulo, Brazil
Phone: +55 19 2103 2860
Fax: +55 19 2103 2862
al.securitysystems@bosch.com
www.boschsecurity.com