

# NWC-0700 and 0800 Megapixel IP Camera S

www.boschsecurity.com



**BOSCH**  
Invented for life



- ▶ 2.0 or 3.1 megapixel resolution versions
- ▶ Selectable resolution and frame rate
- ▶ High quality MJPEG video compression
- ▶ Replaces several fixed-mount analog cameras
- ▶ Integrates with DiBos Hybrid Digital Video Recorder (DVR)

The NWC-0700 and the NWC-0800 Megapixel IP Camera delivers data to, and gets power from, the Ethernet network. The megapixel resolution, combined with high quality image processing, let these cameras operate in extreme lighting conditions from more than 100,000 lux to as low as one lux. Both the frame rate and resolution are adjustable, providing precise fine-tuning of the image quality to accommodate the bandwidth and storage requirements. Adjustable MJPEG compression further reduces the impact on transmission speed and storage. View full resolution images, live or during playback, with the Bosch DiBos 8 Hybrid DVR. Record and monitor as many as four user-defined zoomed areas per camera for closer examination.

## Functions

### Configuration

Configure network parameters and install the camera using a simple user interface with easy-to-understand software. The camera can be equipped with a wide variety of C/CS mount lenses and supports auto-iris lenses.

### Video encoding

The camera produces high-quality streaming video with exceptionally sharp resolution. Advanced MJPEG compression allows the camera to deliver 1600 x 1200 video resolution at up to 24 images per second over its Ethernet connection.

### Network and power

Either camera transfers data at up to 45 Mbit/s over an Ethernet connection and draws power from the network connection (PoE with full 802.3af compliancy) or from a 12 VDC external power source. PoE allows greater placement flexibility and more cost-effective installation, since cameras do not require a local power source. Connecting an uninterruptible power source (UPS) to the PoE switch allows continuous operation and surveillance, even during power failures.

### Operation

These innovative cameras provide high quality image processing that produce sharp images with high detail and outstanding color accuracy. Selectable resolutions and frame rates, combined with adjustable MJPEG compression, allow the best image quality for the given bandwidth or storage restrictions.

## Certifications and approvals

Safety	acc. to EN 60950 (CE)
	acc. to UL 60950-1; CAN/CSA E 60950-1
Immunity	acc. to EN 55024 IT equipment (CE)
Emission	acc. to EN 55022 class A (CE)
	acc. to EN 61000-3-2 (CE); EN 61000-3-3 (CE)
	acc. to FCC CFR 47 Part 15, Class A

Region	Certification	
Europe	CE	Declaration of Conformity
USA	FCC	Declaration of Conformity

## Parts included

Qty	Components
1	NWC-0700 Megapixel IP Camera* or NWC-0800 Megapixel IP Camera*
1	CS to C mount adapter
1	Quick installation guide
1	CD-ROM with manual and Setup/Viewer software
1	1/16 in. hex key for back focus adjustment

\* Lens not included

## Technical specifications

### Electrical

Power Supply	PoE or external	
Rated Voltage (ext.)	12 VDC	
Voltage Range (ext.)	9 to 12 VDC	
Power Consumption	0.5 A	
Connector (ext.)	5 mm, center contact positive	
PoE	IEEE 802.3af compliant RJ45 connector	
Video Compression	MJPEG	
Sensor	½ in. CMOS, color (both models)	
Sensor Matrix		
	• NWC-0700	1600 x 1200
	• NWC-0800	2048 x 1536
Resolution	<b>IPS (NWC-0700)</b>	<b>IPS (NWC-0800)</b>
	• 1280 x 1024	32
	• 1600 x 1200	24
	• 1920 x 1080	NA
	• 1920 x 1200	NA

	• 2040 x 1530	NA	15
<b>Video S/N</b>			
Sensitivity			
	• NWC-0700	0.5 lx at F1.4 (lowlight exposure)	
	• NWC-0800	1.0 lx at F1.4 (lowlight exposure)	
Exposure			
	• High Speed	1 to 10 ms, adjustable	
	• Speed	10 ms (80 ms lowlight)	
	• Balanced	20 ms (80 ms lowlight)	
	• Quality	40 ms (200 ms lowlight)	
	• Moonlight	Up to 500 ms lowlight	
Dynamic Range	60 dB		
BLC	Auto		
Gain	Auto, fixed level selectable		
White Balance	Auto, multimatrix		

### Software Control

Unit Configuration	Via web browser and proprietary software
MJPEG Quality	Selectable, 21 levels
Min. Window Size	32 x 32 pixels
Motion Blurring Correction	On/off
Flicker Control	50/60 Hz, selectable
Firmware	Flash ROM, remote update

### Network

Protocols	HTTP, ARP, UDP, IP, ICMP, TFTP
Ethernet	10/100 Base-T, auto-sensing, half/full duplex, RJ45
Overall Unit Delay	2 frames, 45 ms per frame

### Mechanical

Dimensions (H x W x D)*	63.5 x 76 x 125 mm (2.5 x 3 x 4.9 in.)
Weight*	Approx. 0.45 kg (1 lb)
Mounting	¼ in. tripod on top and bottom
Color	Silver and black
Lens mounting	CS (C-mount with adaptor)

\* Without lens

**Environmental**

Operating Temperature	0 °C to +40 °C (+32 °F to +104 °F)
Storage Temperature	-20 °C to +60 °C (-4 °F to +140 °F)
Humidity	<90% relative humidity (non-condensing)

**Compatibility table for camera / lens / enclosure**

Lens Type	Enclosure Models	
	UHO-HBGS-10	UHI-SBG-0
VLM-0814-MP, 8 mm F1.4, Manual iris	+	+
VLM-1214-MP, 12 mm F1.4, Manual iris	+	+
VLM-1614-MP, 16 mm F1.4, Manual iris	+	+
VLM-2514-MP, 25 mm F1.4, Manual iris	+	+
VLM-3V1228-MP, 12-36 mm F2.8, Manual iris	+	+
VLM-2V0414-MP, 4-8 mm F1.4, Manual iris	+	+
VLG-2V0414-MP, 4-8 mm F1.4, DC iris	+	+

**Legend**

+	Compatible
-	Not compatible.

**Ordering information****NWC-0700 Megapixel IP Camera**

Megapixel Camera, color, 2.0 MP resolution,  
12 VDC/POE  
Order number **NWC-0700**

**NWC-0800 Megapixel IP Camera**

Megapixel Camera, color, 3.1 MP resolution,  
12 VDC/POE  
Order number **NWC-0800**

**Accessories****VLM-2V0414-MP**

Lens 1/2-inch 4-8mm F1.4 C-mount varifocal manual  
iris  
Order number **VLM-2V0414-MP**

**VLG-2V0414-MP**

Lens 1/2-inch 4-8mm F1.4 C-mount varifocal DC iris  
Order number **VLG-2V0414-MP**

**VLM-0814-MP**

Lens 2/3-inch 8 mm F1.4 C-mount monofocal manual  
iris  
Order number **VLM-0814-MP**

**VLM-1214-MP**

Lens 2/3-inch 12 mm F1.4 C-mount monofocal manual  
iris  
Order number **VLM-1214-MP**

**VLM-1614-MP**

Lens 2/3-inch 16 mm F1.4 C-mount monofocal manual  
iris  
Order number **VLM-1614-MP**

**VLM-2514-MP**

Lens 2/3-inch 25 mm F1.4 C-mount monofocal manual  
iris  
Order number **VLM-2514-MP**

**VLM-3V1228-MP**

Lens 2/3-inch 12-36mm F2.8 C-mount varifocal manual  
iris  
Order number **VLM-3V1228-MP**

**Represented by:**

**Americas:**

Bosch Security Systems, Inc.  
130 Perinton Parkway  
Fairport, New York, 14450, USA  
Phone: +1 800 289 0096  
Fax: +1 585 223 9180  
security.sales@us.bosch.com  
www.boschsecurity.us

**Europe, Middle East, Africa:**

Bosch Security Systems B.V.  
P.O. Box 80002  
5617 BA Eindhoven, The Netherlands  
Phone: + 31 40 2577 284  
Fax: +31 40 2577 330  
emea.securitysystems@bosch.com  
www.boschsecurity.com

**Asia-Pacific:**

Robert Bosch (SEA) Pte Ltd, Security  
Systems  
11 Bishan Street 21  
Singapore 573943  
Phone: +65 6571 2808  
Fax: +65 6571 2699  
apr.securitysystems@bosch.com  
www.boschsecurity.asia

**China:**

Bosch (Shanghai) Security Systems Ltd.  
201 Building, No. 333 Fuquan Road  
North IBP  
Changning District, Shanghai  
200335 China  
Phone +86 21 22181111  
Fax: +86 21 22182398  
www.boschsecurity.com.cn

**America Latina:**

Robert Bosch Ltda Security Systems Division  
Via Anhanguera, Km 98  
CEP 13065-900  
Campinas, Sao Paulo, Brazil  
Phone: +55 19 2103 2860  
Fax: +55 19 2103 2862  
latam.boschsecurity@bosch.com  
www.boschsecurity.com