

From
BT-SC/MKP8.1

Product Management

Nuremberg
21.03.2019

Release Letter

Product:	<i>Video Security Client</i>
Version:	<i>2.2.1.43</i>

This letter contains latest information about the above mentioned software.

1. General

Video Security Client is the market's easy to use video surveillance application provided by Bosch for local and remote monitoring of IP cameras and appliances. The software supports small systems from 1 to 16 cameras and is the perfect choice for loss monitoring in supermarkets, boutiques, offices, and hotels. By connecting to one of the Bosch Recording solutions of the DIVAR IP Family all channels provided by the DIVAR IP are supported.

Video Security Client allows to live-monitor and replay IP surveillance cameras anywhere network connection is available. The application supports standalone network cameras or any DIVAR IP family device. As Video Security Client directly connects to the Bosch devices, no local configuration is needed. For a better overview and individual organization, devices are represented as remote sites.

From BT-SC/MKP8.1	Product Management	Nuremberg 21.03.2019
----------------------	--------------------	-------------------------

2. New Features

- None

3. Changes / Bug Fixes

- Fixed crash with long host names

4. Restrictions, known issues

- In case of SSL connection instant one-click recording for H.264/H.265 live video to local disk is currently not supported for FW Version 6.43 and for MIC 9000 with FW Version 6.42
- HTTP/RCP+ connections (including auto update) through HTTP(S) proxies are currently not supported
- Connections to devices of the DIVAR IP Family with VRM Version 3.0 support only transcoded connections
- Audio-Playback is currently not available
- Only BiCom-protocol is for PTZ-commands
- Hardware accelerated decoding is not available on Windows 7
- Local MP4-Video Export does not contain Audio
- Secondary VRM is currently not supported

5. Features and Changes / Bug Fixes with former versions

Changes / Bug Fixes with 2.2.0.36

Maintenance release

Based on your customer feedback, we did some bug fixing and further improved the stability of the client to improve your user experience.

New Features with 2.1

- Build in geographic maps for managing, viewing and navigating cameras
- Viewing Option of georeferenced VCA tracking data on maps
- Hardware accelerated H.265 support
- Support for MIC IP Fusion 9000i cameras

From BT-SC/MKP8.1	Product Management	Nuremberg 21.03.2019
----------------------	--------------------	-------------------------

- Viewing option for single cameras connected to the Bosch Remote Portal without the need of a DIVAR IP
- Instant one-click recording for H.264/H.265 live video to local disk (mp4)

Changes / Bug Fixes with 2.1

- Fixed displayed time string in HTML export

New Features with 1.1

- Modern and Easy to use video security client for 1 to 16 standalone-cameras and up to 16 sites. Connecting to a DIVAR IP all channels are displayed. Due to the fact of screen layout a max. of eight SW windows (cameos) can be opened at the same time.
- Client-site dewarping for FLEXIDOME IP panoramic devices
- Flexible Window-Layout
- Advanced Forensics search-capabilities with detailed activity graph
- Support of mouse and touch gestures
- Scales from Desktop to mobile devices

From
BT-SC/MKP8.1

Product Management

Nuremberg

21.03.2019

6. System Requirements

Minimum System Requirements	Description
Memory	2 GB or greater
Hard Disk	100 MB of Disk Space
Processor	1.5 GHz (Dual-Core) or faster
Operating System	Windows 7 (32- and 64-bit edition) Windows 8 (32- and 64-bit edition) Windows 10 (32- and 64-bit edition) Windows Server 2012
Graphics Card	For hardware accelerated decoding Windows 8.x and any DirectX 11 GPU (e. g. Intel HD Graphics 2000 or higher) is required.
Minimum Display Resolution	1024 x 600 px