

From	Product Manager	Telephone	Nuremberg
STVC/PRM		+49 911 93456 0	07.08.2008

## Release Letter

Product:	<b><i>MPEG-ActiveX</i></b>
Version:	<b><i>3.03.0009</i></b>

This letter contains latest information about the above mentioned software version.

This version is a maintenance release to version 3.02 and thus provides the same feature set as well as the same performance values.

### 1. Changes

- This MPEG-ActiveX allows showing video while both the VIDOS Lite Viewer and a Web browser displaying a FW 3.5x BVIP unit's Web page are running on the same PC.

From STVC/PRM	Product Manager	Telephone +49 911 93456 0	Nuremberg 07.08.2008
------------------	-----------------	------------------------------	-------------------------

## 2. Restrictions; Known Issues

- For 32-bit color mode the PC must support YUV overlay.
- MPEG-ActiveX versions 2.7x and newer cannot display the live video of a VideoJet 400 in quad mode anymore when local recording for more than one camera is active.
- For MPEG-2 rendering on Nvidia graphic cards, use driver version 71.84 or older for optimal performance.
- In display mode “Dual view” on Nvidia FX1400/4400 and ATI GL V 3100 graphic cards, drag & drop from primary to secondary monitor and vice versa does not automatically refresh camera images.
- Streaming works only if a RCP+ connection is established. If multicast streaming is enabled, a device can only connect to the stream if a RCP+ connection exists. Although the multicast address is enabled, the IP address must be set in addition.

## 3. System Requirements

- Desktop: Personal Computer
- CPU: Pentium IV, 1.8 GHz
- RAM: 256 MByte
- OS: Windows 98/2000/XP
- Graphic card: Nvidia Geforce6600, Nvidia Quadro FX1400, ATI RADEON 9800/X600/X800, Matrox Parhelia or better
- Ethernet card: 100 MBit/s
- Sound card: yes if audio required
- Software: DirectX 9.0c