

EX8 Series Dual Sensor Ceiling Camera

www.boschsecurity.com



BOSCH
Invented for life



- ▶ Sleek, vandal-resistant housing with dual CCD images
- ▶ Sensors for bi-directional surveillance performance
- ▶ Dual CCD design for imaging from front and rear of camera
- ▶ Pan/tilt/twist hand-adjustable gimbals require no tools for maximum ease of installation
- ▶ Detachable camera platform for fast and easy CCD adjustments

The EX8 is an installer-friendly, vandal resistant ceiling mount camera that incorporates dual CCD image sensors for versatile bi-directional surveillance. The EX8 is ideal for use in hallways and corridors where it is important to view activity in two directions. The EX8 is available with an M4 mechanical filter LXR CCD, for vivid daytime color and excellent performance under infrared illumination.

The EX8 is designed with installer friendly features, including Pan/tilt/twist camera gimbals for quick and easy CCD and lens adjustments. The hand-adjustable gimbals require no tools and help minimize installation time. With Pan/tilt/twist gimbals, dealers can quickly and easily achieve perfectly horizontal pictures with a simple twist.

Installers will appreciate the EX8's detachable camera platform which allows the housing base to be mounted separately from the camera platform. With this feature, dealers are now free to adjust the optics at a location safer or more convenient than the ceiling.

The EX8 also includes a Video Patch Lead (VPL) for convenient installations. With the VPL, installers can connect portable LCD monitors directly into the EX8 for instant video confirmation of camera positioning. The EX8 operates in 12 VDC or 24 VAC and is conduit compatible for easy installation onto standard electrical fixtures for complete cable-management.

Constructed of die-cast aluminum, the EX8 provides outstanding optical performance in a sleek, vandal-resistant housing designed for all-weather conditions. Small and compact, the EX8 is large enough to accommodate varifocal 4-8 mm lenses. The EX8 is ideal for front and rear surveillance at any number of applications including schools and colleges, prisons, banks, transportation hubs and casinos.

Functions

Applications

- Prisons
- Schools and colleges
- Hospitals
- Airports
- Transportation hubs
- Casinos
- Offices
- Transit vehicles

Certifications and approvals

Region	Certification
Belgium	INCERT B-509-0005

Technical specifications

Video

Sensor	M4 High Resolution Day/Night CCD	C7 High Resolution Color CCD
Resolution	540 TVL color / 540 TVL monochrome	500 TVL
Effective Pixels NTSC (H x V)	768 x 494	768 x 494
Effective Pixels PAL (H x V)	752 x 582	752 x 582
Sensitivity	0.06 Lux with F1.4 lens	2.7 Lux at F1.4
S/N Ratio	Greater than 48dB (AGC off)	Greater than 48dB

Output Signal	1 Vpp, 75 ohm
Gamma	0.45
Gain Control	AGC (with on/off switch)
Electronics Iris	1/60 to 1/100,000 (NTSC)
	1/50 to 1/100,000 (PAL)

Mechanical

Construction	Die-cast aluminum
Window	3/16 inch polycarbonate
Weight	1.4 kg (3.1 lbs)
Overall Dimension	286 x 138 x 95 mm (11.3 x 5.4 x 3.7 in.)

Electrical

Voltage	12 to 24 AC/DC
Power Draw	190 mA x 2 = 380 mA at 12 VDC

Environmental

Operational Range	-25°C to +60°C (-13°F to 140°F)
-------------------	---------------------------------

Ordering information

EX8C7V0409-N Dual Sensor Ceiling Camera

Dual sensor ceiling camera, 1/3 in. hi-res color, 500 TVL, 4-9 mm lens, NTSC
Order number **EX8C7V0409-N**

EX8C7V0409-P Dual sensor Ceiling camera

Dual sensor ceiling camera, 1/3 in. hi-res color, 500 TVL, 4-9 mm lens, PAL
Order number **EX8C7V0409-P**

EX8C7V0922-N Dual Sensor Ceiling Camera

Dual sensor ceiling camera, 1/3 in. hi-res color, 500 TVL, 9-22 mm lens, NTSC
Order number **EX8C7V0922-N**

EX8C7V0922-P Dual Sensor Ceiling Camera

Dual sensor ceiling camera, 1/3 in. hi-res color, 500 TVL, 9-22 mm lens, PAL
Order number **EX8C7V0922-P**

EX8M4V0409-N Dual Sensor Ceiling Camera

Dual sensor ceiling camera, 1/3 in. hi-res day/night, 540/540 TVL, 4-9 mm lens, NTSC
Order number **EX8M4V0409-N**

EX8M4V0409-P Dual Sensor Ceiling Camera

Dual sensor ceiling camera, 1/3 in. hi-res day/night, 540/540 TVL, 4-9 mm lens, PAL
Order number **EX8M4V0409-P**

EX8M4V0922-N Dual Sensor Ceiling Camera

Dual sensor ceiling camera, 1/3 in. hi-res day/night, 540/540 TVL, 9-22 mm lens, NTSC
Order number **EX8M4V0922-N**

EX8M4V0922-P Dual Sensor Ceiling Camera

Order number **EX8M4V0922-P**

Accessories

EXPS.008 VAC Power Supply

Power supply 120 VAC/ 24 VAC 1500 mA
Order number **EXPS.008**

PSU-230-24 Power Supply

Power Supply, 230 VAC / 24 VAC, 50 W
Order number **PSU-230-24**

Represented by:

Americas:

Bosch Security Systems, Inc.
130 Perinton Parkway
Fairport, New York, 14450, USA
Phone: +1 800 289 0096
Fax: +1 585 223 9180
security.sales@us.bosch.com
www.boschsecurity.us

Europe, Middle East, Africa:

Bosch Security Systems B.V.
P.O. Box 80002
5617 BA Eindhoven, The Netherlands
Phone: + 31 40 2577 284
Fax: +31 40 2577 330
emea.securitysystems@bosch.com
www.boschsecurity.com

Asia-Pacific:

Robert Bosch (SEA) Pte Ltd, Security
Systems
11 Bishan Street 21
Singapore 573943
Phone: +65 6571 2808
Fax: +65 6571 2699
apr.securitysystems@bosch.com
www.boschsecurity.asia

China:

Bosch (Shanghai) Security Systems Ltd.
201 Building, No. 333 Fuquan Road
North IBP
Changning District, Shanghai
200335 China
Phone +86 21 22181111
Fax: +86 21 22182398
www.boschsecurity.com.cn

America Latina:

Robert Bosch Ltda Security Systems Division
Via Anhanguera, Km 98
CEP 13065-900
Campinas, Sao Paulo, Brazil
Phone: +55 19 2103 2860
Fax: +55 19 2103 2862
latam.boschsecurity@bosch.com
www.boschsecurity.com