

LTC 0335 Series Dinion Monochrome Cameras

www.boschsecurity.com



BOSCH

Invented for life



- ▶ 1/3-inch format CCD imager
- ▶ High sensitivity
- ▶ Advanced digital signal processing
- ▶ Standard resolution
- ▶ Auto detection of lens type

The LTC 0335 Series are compact, rugged, 1/3-inch image format digital monochrome CCD cameras. Their superior sensitivity and resolution provide optimal performance in virtually all environments. Easy Installation, digital signal processing, on screen displays, superior picture quality and reliability brings the video performance of standard resolution monochrome cameras to a level never reached before. The LTC 0335 Series is the best choice for first time and professional users.

The LTC 0335 camera also comes with a lens wizard that automatically detects the type of lens installed. An OSD guide that allows the installer to easily adjust the lens level and focus without special tools or filters. The ability to operate on AC or DC provides added flexibility to system designs and reduces the amount of training and support items to keep on-hand.

This fully automatic camera is ready to work for you, and is easy to install in even the most demanding applications.

On-screen Displays (OSD) provide quick and easy access to all camera features.

Functions

Bilinx Technology

The LTC 0335 Series cameras incorporate Bilinx. Bilinx is a bidirectional communication capability embedded in the video signal of all Bosch Dinion cameras. With Bilinx technicians can check status, change camera settings and even update firmware from virtually anywhere along the video cable. Bilinx reduces service and installation time, provides for more accurate set-up and adjustment, and improves overall performance. In addition, Bilinx uses the standard video cable to transmit alarm and status messages, providing superior performance without additional installation steps.

Certifications and approvals

Electromagnetic Compatibility

EMC Immunity: According EN50130-4

EMC Emission: According EN505022 class B

According FCC, class B part 15

Safety

LTC 0335/10 and LTC 0335/50: EN60065

LTC 0335/20 and LTC 0335/60: UL6500

Region	Certification	
Europe	CE	Declaration of Conformity
USA	FCC	Declaration of Conformity

Parts included

Quantity	Component
1	LTC 0335 Series Monochrome Camera
1	Spare male 4-pin lens connector
	Lens not included

Technical specifications**Electrical**

Model No.	Rated Voltage	Voltage Range	System
LTC 0335/10	12 VDC	10.8–39 VDC	CCIR
	24 VAC 50 Hz	12–28 VAC 45–65 Hz	CCIR
LTC 0335/20	12 VDC	10.8–39 VDC	EIA
	24 VAC 60 Hz	12–28 VAC 45–65 Hz	EIA
LTC 0335/50	230 VAC 50 Hz	85–265 VAC 45–65 Hz	CCIR
LTC 0335/60	120 VAC 60 Hz	85–265 VAC 45–65 Hz	EIA

Power Consumption	4 W, excluding lens
Imager	Interline transfer CCD
	1/3-inch image format

Active Pixels

CCIR Models:	512 H x 582 V
EIA Models:	512 H x 492 V

Sensitivity (3200K, F1.2, 89% scene reflectance)

	Usable Picture (50 IRE)	Full Video
Scene Illumination ¹⁾	0.12 lux (0.01 fc)	0.48 lux (0.048 fc)
Imager Illumination	0.024 lux (0.0024 fc)	0.10 lux (0.010 fc)
Horizontal Resolution	380 TVL	

Signal-to-Noise Ratio	50 dB
Gain	Auto, 21 dB (max)
Electronic Shutter	Automatic, 1/50 to 1/500000 sec. (CCIR), 1/60 to 1/600000 sec. (EIA)
Aperture Correction	Horizontal and vertical, symmetrical
Backlight Compensation	Center window weighting
Video Output	Composite video 1.0 Vpp, 75 Ohm

Synchronization

Line-lock	(When powered by AC only) Synchronizes the camera to the power line zero crossing for roll-free vertical interval switching. Vertical phase delay can be adjusted (0–358 degrees) to allow vertical synchronization in multi-phase power installations.
Crystal-lock	(When DC-supply or L/L off) Internal crystal reference is standard on all models.

Controls

Video level	
Shutter: AES / off / flickerless	
AGC: on / off	
BLC: on / off	
Auto black: on / off	
Vphase adjustment: 0–358 degrees	

Mechanical

Connectors	Video output: BNC
	Video/DC-IRIS connector: 4-pin EIA-J
Power	
LTC 0335/10 and LTC 0335/20	Push type connectors, polarity independent, isolated from video output terminals
LTC 0335/50	2-wire Power cord with Euro plug
LTC 0335/60	2-wire Power cord with polarized plug
Tripod Mount	Top and bottom, 1/4-inch 20 UNC
Lens Mount	CS (maximum lens protrusion 5 mm, 0.2 in), C-mount compatible (with optional adapter ring)
Dimensions (H x W x D)	58 x 66 x 122 mm (2.28 x 2.6 x 4.8 in.) including connectors
Weight	0.45 kg (0.99 lb)

Environmental

Operating Temperature	-20 °C to 50 °C (-4 °F to 122 °F)
Storage Temperature	-25 °C to 70 °C (-13 °F to 158 °F)
Operating Humidity	5% to 93% non-condensing

Ordering information**LTC 0335/10 Dinion Monochrome Camera**

1/3-inch B/W CCIR, DSP, 380 TVL, 12 VDC/24VAC, 50 Hz

Order number **LTC0335/10**

LTC 0335/50 Dinion Monochrome Camera

1/3-inch B/W CCIR, DSP, 380 TVL, 230 VAC, 50 Hz

Order number **LTC0335/50**

Accessories**TC120PS Power Supply Unit**

Order number **TC120PS**

TC220PS Power Supply Unit

Order number **TC220PS**

TC220PSX-24 Power Supply Unit

Order number **TC220PSX-24**

TC1334 Power Supply Unit

Order number **TC1334**

S1374 Adapter

converts C mount lens to CS mount camera

Order number **S1374**

Represented by:**Americas:**

Bosch Security Systems, Inc.
130 Perinton Parkway
Fairport, New York, 14450, USA
Phone: +1 800 289 0096
Fax: +1 585 223 9180
security.sales@us.bosch.com
www.boschsecurity.us

Europe, Middle East, Africa:

Bosch Security Systems B.V.
P.O. Box 80002
5617 BA Eindhoven, The Netherlands
Phone: + 31 40 2577 284
Fax: +31 40 2577 330
emea.securitysystems@bosch.com
www.boschsecurity.com

Asia-Pacific:

Robert Bosch (SEA) Pte Ltd, Security Systems
11 Bishan Street 21
Singapore 573943
Phone: +65 6571 2808
Fax: +65 6571 2699
apr.securitysystems@bosch.com
www.boschsecurity.asia

China:

Bosch (Shanghai) Security Systems Ltd.
201 Building, No. 333 Fuquan Road
North IBP
Changning District, Shanghai
200335 China
Phone +86 21 22181111
Fax: +86 21 22182398
www.boschsecurity.com.cn

America Latina:

Robert Bosch Ltda Security Systems Division
Via Anhanguera, Km 98
CEP 13065-900
Campinas, Sao Paulo, Brazil
Phone: +55 19 2103 2860
Fax: +55 19 2103 2862
latam.boschsecurity@bosch.com
www.boschsecurity.com